



Water Quality Measurement Instrument

- **Product type**
Attended, Unattended
- **Parameters measured**
Temperature, Conductivity, Depth, pH, Dissolved Oxygen (LDO), Turbidity, ORP, Blue-Green Algae, Chlorophyll a
- **Product Highlights**
The next generation multiparameter water quality instrument
- **Interface**
SDI-12, RS-485, RS-232, TTY, USB

The HYDROLAB HL7 multiparameter sonde offers a versatile, durable and practical solution to the day to day needs of monitoring programs for both simple and complex deployments. With a large sensor suite, it is able to thrive in demanding environmental conditions for long term continuous and profile monitoring.

Bio-fouling is minimized when equipped with the central cleaning brush and performance is maximized with an advanced power management system. It has a temperature sensor, seven external sensor ports and an optional internal depth sensor.

It helps our customers to correctly log data autonomously and easily integrate into real time telemetry systems.

Technical Data

Hydrolab HL7 - Multiparametrová sonda

Sensor Ports		9 sensor ports available
Dimensions	Diameter: 8.9 cm (3.5 in.) without rubber bumpers; 9.8 cm (3.85 in.) with rubber bumpers	
Length:	66.4 cm (26.1 in.)	
Weights	4.5 kg (10 lb) with four Dcell batteries, storage/calibration cup with no liquid	
Power Requirements		6...24 VDC (12 VDC nominal) applied to the communications module, 12 VDC:2.0 W average, 24 W peak
Battery Life*		90 days
Operating Temperature	-5 to 50 °C (23 to 122 °F), nonfreezing	
Storage Temperature	1 to 50 °C (34 to 122 °F)	
Depth		200 m (656 ft) maximum
Data Memory	4 GB	
Tensile strength	(Maximum) Mooring cap: 68 kg (150 lb); deployment cable: 227 kg (500 lb)	
Communications		Communications module: USB, SDI12, RS232 Modbus, RS485 Modbus and RS232 TTY
Sampling Rate	1 Hz minimum, (once per second)	

2-2

We reserve the right to make technical changes and improvements without notice. V-26/04/2024
OTT Hydromet GmbH, Germany